






**SPECIFICATION DATA SHEET | MODEL : 20TCG**



The **TRANSCUBE™ 20TCG** is a multi-task on-site fuel deployment solution for the direct supply to stationary diesel engines or the refueling of equipment on demand.

-  **Transportable.** Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.
-  **Stackable.** Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.
-  **Accessible.** Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.
-  **Efficient.** Lockable equipment cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel-powered equipment.
-  **Environmentally Safe.** Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

<b>SPECIFICATIONS*</b>	
STANDARD FITTINGS: High accuracy contents gauge; 3" Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent.	
OPTIONAL FITTINGS: Complete transfer pump kits; water & particulate filter kits; fuel up to (2) feed & return blocks; fuel hose & quick couplers.	
<b>Capacity (Brim-Fill) Litres:</b> 2091	<b>Dimension Height (mm/in):</b> 1319 mm/51.91"
<b>Capacity (Brim-Fill) Imperial Gallons:</b> 460	<b>Weight Empty (lbs/kg):</b> 1815 lbs (823kg)
<b>Capacity (Brim-Fill) US Gallons:</b> 552	<b>Weight Full (lbs/kg):</b> 6424 lbs (2914kg)
<b>Dimension Length (mm/in):</b> 2292 mm/90.24"	<b>Approvals:</b> UL142, ULC S-601-07, SUN IBC Type 31A,
<b>Dimension Width (mm/in):</b> 1140 mm/44.88"	UN DOT, NFPA, Transport Canada, Vlare, Kiwa

\*Model specifications may slightly differ based on stock availability in your area. Please contact your local representative to confirm tank specifications.