




SPECIFICATION DATA SHEET | MODEL : 100TCG



The **TRANSCUBE™** Standby 100TCG is the solution to all your fuel delivery needs; On-site equipment refueling, direct back-up supply for diesel engines powering generators, compressors, pumps, HVAC.... and more!

-  **Accessible.** Access manway for maintenance and inspection of inner tank. Four-way forklift pockets for easy lifting when empty.
-  **Efficient.** Lockable equipment cabinet locks and secures equipment and fuel ports to run up to 2 pieces of diesel-powered equipment with a 3-point locking system and letterbox-style ports.
-  **Environmentally Safe.** Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

SPECIFICATIONS

STANDARD FITTINGS: High accuracy contents gauge; 3" Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent.
 OPTIONAL FITTINGS: Complete transfer pump kits; water & particulate filter kits; additional set of feed & return blocks; fuel hose & quick couplers.

Capacity (Optimum / Safe fill) Litres: 9,040 / 8,588	Bund Material Thickness (in): 1/8" (3 mm)
Capacity (Optimum / Safe fill) Imperial Gallons: 1,988 / 1,889	Inner Tank Material Thickness (in): 1/4" (6 mm)
Capacity (Optimum / Safe fill) US Gallons: 2,388 / 2,269	Weight Empty (lbs/kg): 7,600 lbs (3,450kg)
Dimension Length (mm/in): 2514 mm/99"	Weight Full (lbs/kg): 27,362 lbs (12,411kg)
Dimension Width (mm/in): 2261 mm/89"	Approvals: UL142, ULC S-601-07, NFPA 30A
Dimension Height (mm/in): 2566 mm/101"	