

WINCO®

Quality Generators Since 1927



HPS6000HE

EPA
APPROVED

Engine:

- Honda GX340 OHV
- EPA certified design for use with gasoline or natural gas
- Commercial grade engine with cast iron cylinder sleeves
- 3 year warranty
- Special carburetor and secondary gas regulator allows the engine to operate on the most convenient fuel - gasoline or natural gas
- Maintenance-free electronic ignition system
- Low oil protection helps prevent costly repairs and downtime

Generator End:

- 100% copper windings - longer life and improved motor starting
- Dampers, skewed rotors for <6% harmonic distortion
- Capacitor excitation for brushless operation

Components:

- 7 gallon steel fuel tank with fuel gauge
- Heavy duty 1"-14 gauge tubular steel cradle
- Industrial powder coat paint
- Electric/Recoil start (NG operation requires electric start)
- Full receptacle package with circuit breaker protection
- 120/240 volt receptacle for connection to a temporary power distribution system or to a building electrical service with an approved manual transfer switch for emergency/standby use
- Vibration isolation for smooth operation
- Easy to move, convenient to store


Accessories (optional):

- Two-wheel dolly kit
- Generator cover
- Low pressure fuel solenoid kit
- WINCO manual transfer switch
- Plug-in line voltage monitor
- 30 amp (NEMA L14-30P) plug

| | |
|--|--|
| SURGE WATTS ⁽¹⁾ | 6000 |
| CONTINUOUS WATTS ⁽¹⁾ | 5500 |
| AMPS ⁽¹⁾ | 45.8/22.9 |
| VOLTS | 120/240 |
| VOLTAGE REGULATION | +/- 5% |
| FREQUENCY REGULATION | +/- 3% |
| ENGINE BRAND | HONDA |
| ENGINE MODEL | GX340 |
| ENGINE STARTER ⁽³⁾ | ELECTRIC/RECOIL |
| ENGINE SPEED | 3600 RPM |
| DISPLACEMENT | 389 CC |
| ENGINE CYLINDERS | SINGLE |
| LOW OIL PROTECTION | STANDARD |
| dBAAT 7 METERS | 72 |
| FUEL TANK | 7 GAL |
| FUEL USE: GASOLINE | 1.0 gal/hr |
| NATURAL GAS | 160 ft ³ /hr - 163,200 BTU/hr |
| MOTOR STARTING (CODE G) ^{(1) (2)} | 2 HP |
| MAIN CIRCUIT BREAKER | 25A |
| 120 VOLT RECEPTACLES | 2 x NEMA 5-20R 20A |
| 120/240 VOLT RECEPTACLES | 1 x NEMA L14-30R 30A |
| DIMENSIONS (LxWxH) | 32.75" x 22.5" x 22" |
| NET WEIGHT | 202 lbs |
| SHIP WEIGHT | 224 lbs |
| WARRANTY (ENG/GEN) ⁽⁴⁾ | 3 YRS / 2 YRS |

NOTES: (1) Based on gasoline fuel. Derate 20% for Natural Gas. (2) Code G capacitor start motor. (3) Electric start models include battery rack and cables, battery not included. BCI Group 20 or 24HL, 12-volt, 300 CCA battery required. (4) Prime Power Warranty 120 days. Contact your local Honda engine service center for engine warranty assistance.

Presented by:

BI-FUEL  NATURAL GAS
GASOLINE

HOME POWER®

Toll Free: 1-800-733-2112
sales@wincogen.com

www.wincogen.com

225 South Cordova Avenue
Le Center MN, 56057